



|                |               |
|----------------|---------------|
| <b>Symbol:</b> | RSSM101A2C3RD |
|----------------|---------------|

|                        |                 |
|------------------------|-----------------|
| <b>Product groups:</b> | Rocker Switches |
|------------------------|-----------------|

## Product specifications

|                                 |              |
|---------------------------------|--------------|
| <b>Type of switch:</b>          | ROCKER       |
| <b>Contacts configuration:</b>  | SPST         |
| <b>Number of positions:</b>     | 2            |
| <b>Stable positions number:</b> | 2            |
| <b>Switching method:</b>        | ON-OFF       |
| <b>AC contacts rating @R:</b>   | 3A / 250V AC |
| <b>Key button colour:</b>       | red          |
| <b>Illumination:</b>            | neon lamp    |

|                                  |                  |
|----------------------------------|------------------|
| <b>Backlight colour:</b>         | red              |
| <b>Max. contact resistance::</b> | 35mΩ             |
| <b>Body colour:</b>              | black            |
| <b>Leads:</b>                    | connectors       |
| <b>Leads dimensions:</b>         | 4.8x0.8mm        |
| <b>Electrical life:</b>          | 10000 cycles     |
| <b>Mounting hole diameter:</b>   | 19.2x13mm        |
| <b>Button marking:</b>           | O-I              |
| <b>Shape:</b>                    | rectangular      |
| <b>Body dimensions:</b>          | 18.8x12.9x14.4mm |
| <b>Height above panel:</b>       | 5.8mm            |
| <b>Operating temperature:</b>    | -30...80°C       |
| <b>Related items:</b>            | RSC07            |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.005 kg |
|----------------------|----------|