



| | |
|----------------|--------------|
| Symbol: | TUL-NI-00508 |
|----------------|--------------|

| | |
|------------------------|----------------------------------|
| Product groups: | Bootlace ferrule and butt splice |
|------------------------|----------------------------------|

Product specifications

| | |
|---------------------|------------------|
| Type of tip: | bootlace ferrule |
|---------------------|------------------|

| | |
|-------------------------|---------------|
| Ferrule variant: | non-insulated |
|-------------------------|---------------|

| | |
|--------------------------|--------|
| Contact material: | copper |
|--------------------------|--------|

| | |
|----------------------------|--------------------|
| Wire cross-section: | 0.5mm ² |
|----------------------------|--------------------|

| | |
|--------------------|-----|
| Bit length: | 8mm |
|--------------------|-----|

| | |
|-------------------------|--------|
| Contact plating: | tinned |
|-------------------------|--------|

| | |
|-----------------------------|---------|
| Electrical mounting: | crimped |
|-----------------------------|---------|

| | |
|-----------------------------|-------------|
| Conform to the norm: | DIN 46228-1 |
|-----------------------------|-------------|

Additional information

| | |
|----------------------|------|
| Gross weight: | 0 kg |
|----------------------|------|

<https://ninigi.com/cn/en/product/ninigi/bootlace-ferrule-and-butt-splice/tul-ni-00508/100041>