



|                |         |
|----------------|---------|
| <b>Symbol:</b> | NCDG-12 |
|----------------|---------|

|                        |                          |
|------------------------|--------------------------|
| <b>Product groups:</b> | Raster signal connectors |
|------------------------|--------------------------|

## Product specifications

|                           |            |
|---------------------------|------------|
| <b>Type of connector:</b> | wire-board |
|---------------------------|------------|

|                   |      |
|-------------------|------|
| <b>Connector:</b> | plug |
|-------------------|------|

|                           |        |
|---------------------------|--------|
| <b>Kind of connector:</b> | female |
|---------------------------|--------|

|                        |    |
|------------------------|----|
| <b>Number of pins:</b> | 12 |
|------------------------|----|

|                             |           |
|-----------------------------|-----------|
| <b>Mechanical mounting:</b> | for cable |
|-----------------------------|-----------|

|                        |        |
|------------------------|--------|
| <b>Contacts pitch:</b> | 2.54mm |
|------------------------|--------|

|                                 |      |
|---------------------------------|------|
| <b>Connector pinout layout:</b> | 1x12 |
|---------------------------------|------|

|                             |         |
|-----------------------------|---------|
| <b>Flammability rating:</b> | UL94V-0 |
|-----------------------------|---------|

|                           |              |
|---------------------------|--------------|
| <b>Connector variant:</b> | w/o contacts |
|---------------------------|--------------|

|                                |            |
|--------------------------------|------------|
| <b>Locking system:</b>         | latch      |
| <b>Max. operating voltage:</b> | 0.25kV     |
| <b>Enclosure material:</b>     | PBT        |
| <b>A dimension:</b>            | 30.5mm     |
| <b>B dimension:</b>            | 27.9mm     |
| <b>Operating temperature:</b>  | -25...85°C |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.001 kg |
|----------------------|----------|