



| | |
|----------------|---------|
| Symbol: | NS25-G7 |
|----------------|---------|

| | |
|------------------------|--------------------------|
| Product groups: | Raster signal connectors |
|------------------------|--------------------------|

Product specifications

| | |
|---------------------------|------------|
| Type of connector: | wire-board |
|---------------------------|------------|

| | |
|-------------------|------|
| Connector: | plug |
|-------------------|------|

| | |
|---------------------------|--------|
| Kind of connector: | female |
|---------------------------|--------|

| | |
|------------------------|---|
| Number of pins: | 7 |
|------------------------|---|

| | |
|-----------------------------|------|
| Manufacturer series: | NS25 |
|-----------------------------|------|

| | |
|------------------------|----|
| Current rating: | 3A |
|------------------------|----|

| | |
|-----------------------|--------|
| Rated voltage: | 0.25kV |
|-----------------------|--------|

| | |
|-----------------------------|-----------|
| Mechanical mounting: | for cable |
|-----------------------------|-----------|

| | |
|------------------------|--------|
| Contacts pitch: | 2.54mm |
|------------------------|--------|

| | |
|---------------------------------|--------------|
| Connector pinout layout: | 1x7 |
| Flammability rating: | UL94V-0 |
| Connector variant: | w/o contacts |
| Enclosure material: | polyamide |
| A dimension: | 15.24mm |
| B dimension: | 17.78mm |
| Operating temperature: | -25...85°C |

Additional information

| | |
|----------------------|----------|
| Gross weight: | 0.001 kg |
|----------------------|----------|