



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | RS2013C3BK      |
| <b>Product groups:</b> | Rocker Switches |

## Product specifications

|                                  |               |
|----------------------------------|---------------|
| <b>Type of switch:</b>           | ROCKER        |
| <b>Contacts configuration:</b>   | DPST          |
| <b>Number of positions:</b>      | 2             |
| <b>Stable positions number:</b>  | 2             |
| <b>Switching method:</b>         | ON-OFF        |
| <b>AC contacts rating @R:</b>    | 15A / 250V AC |
| <b>Key button colour:</b>        | black         |
| <b>Illumination:</b>             | none          |
| <b>Max. contact resistance::</b> | 35mΩ          |
| <b>Body colour:</b>              | black         |
| <b>Leads:</b>                    | connectors    |
| <b>Leads dimensions:</b>         | 6.3x0.8mm     |
| <b>Electrical life:</b>          | 10000 cycles  |
| <b>Mounting hole diameter:</b>   | 31x22.3mm     |

|                               |             |
|-------------------------------|-------------|
| <b>Button marking:</b>        | O-I         |
| <b>Button shape:</b>          | rectangular |
| <b>Height above panel:</b>    | 9.4mm       |
| <b>Operating temperature:</b> | -30...80°C  |
| <b>Related items:</b>         | RSC09       |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.013 kg |
|----------------------|----------|