



**Symbol:** SR2412519.2F

**Product groups:** Rotary Switches

## Product specifications

|                                 |               |
|---------------------------------|---------------|
| <b>Type of switch:</b>          | rotary        |
| <b>Number of positions:</b>     | 5             |
| <b>Stable positions number:</b> | 5             |
| <b>AC contacts rating @R:</b>   | 1A / 250V AC  |
| <b>Poles number:</b>            | 2             |
| <b>Indexed positions:</b>       | 36°           |
| <b>Leads:</b>                   | for soldering |
| <b>Contact material:</b>        | brass         |

|                                    |              |
|------------------------------------|--------------|
| <b>Max. contact resistance::</b>   | 50mΩ         |
| <b>Body material:</b>              | polyamide 66 |
| <b>Min. insulation resistance:</b> | 0.1GΩ        |
| <b>Mechanical durability:</b>      | 10000 cycles |
| <b>Shaft surface:</b>              | D spring     |
| <b>Shaft diameter:</b>             | 6.35mm       |
| <b>Shaft length:</b>               | 19.2mm       |
| <b>Fastening thread:</b>           | 3/8"-32NEF   |
| <b>Switching torque:</b>           | 6.86Ncm      |
| <b>Operating temperature:</b>      | -20...70°C   |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.008 kg |
|----------------------|----------|