



**Symbol:** TB-5.0-P-3P/BL

**Product groups:** Terminal blocks

## Product specifications

**Type of connector:** PCB terminal block

**Connector:** terminal

**Current rating:** 16A

**Rated voltage:** 0.25kV

**Spatial orientation:** angled 90°

**Connector variant:** with wire protector

**Mechanical mounting:** on PCBs

**Electrical mounting:** screw terminal, THT

**Contact material:** brass

**Contact plating:** tinned

<b>Colour:</b>	blue
<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	PBT
<b>Depth:</b>	7.6mm
<b>Length:</b>	15mm
<b>Connector pinout layout:</b>	1x3
<b>Wire cross-section:</b>	1.5mm <sup>2</sup>
<b>Contacts pitch:</b>	5mm
<b>Number of ways:</b>	3
<b>Height:</b>	10mm
<b>Stripped wire length:</b>	5mm
<b>Connectors features:</b>	assembling possibility
<b>Conform to the norm:</b>	CE
<b>Soldering temperature:</b>	250°C / 5 s
<b>Operating temperature:</b>	-30...120°C

## Additional information

<b>Gross weight:</b>	0.002 kg
----------------------	----------