



| | |
|------------------------|-----------------|
| Symbol: | TBG-5-PB-3P/GN |
| Product groups: | Terminal blocks |

Product specifications

| | |
|-----------------------------|--------------------------|
| Type of connector: | pluggable terminal block |
| Connector: | socket |
| Kind of connector: | male |
| Current rating: | 15A |
| Rated voltage: | 0.3kV |
| Number of pins: | 3 |
| Spatial orientation: | straight |
| Connector variant: | without side walls |
| Mechanical mounting: | on PCBs |
| Electrical mounting: | THT |
| Contact material: | brass |
| Contact plating: | tinned |
| Colour: | green |
| Flammability rating: | UL94V-0 |
| Body material: | polyamide |
| Depth: | 8mm |

Product card TBG-5-PB-3P/GN

| | |
|---------------------------------|------------------------|
| Length: | 15.24mm |
| Connector pinout layout: | 1x3 |
| Contacts pitch: | 5.08mm |
| Number of ways: | 3 |
| Locking system: | latch |
| Height: | 12.3mm |
| Connectors features: | assembling possibility |
| Soldering temperature: | 250°C / 5 s |
| Operating temperature: | -40...105°C |

Additional information

| | |
|----------------------|----------|
| Gross weight: | 0.001 kg |
|----------------------|----------|