

## Product card TBW-5-8P/GN

---



<b>Symbol:</b>	TBW-5-8P/GN
<b>Product groups:</b>	Terminal blocks

### Product specifications

<b>Type of connector:</b>	pluggable terminal block
<b>Connector:</b>	plug
<b>Kind of connector:</b>	female
<b>Current rating:</b>	15A
<b>Rated voltage:</b>	0.3kV
<b>Spatial orientation:</b>	straight
<b>Mechanical mounting:</b>	for cable
<b>Electrical mounting:</b>	screw terminal
<b>Contact material:</b>	brass
<b>Contact plating:</b>	tinned
<b>Colour:</b>	green
<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	polyamide
<b>Depth:</b>	17.7mm
<b>Length:</b>	40.64mm
<b>Connector pinout layout:</b>	1x8

## Product card TBW-5-8P/GN

---

<b>Wire cross-section:</b>	2.5mm <sup>2</sup>
<b>Contacts pitch:</b>	5.08mm
<b>Number of ways:</b>	8
<b>Locking system:</b>	latch
<b>Number of terminals:</b>	8
<b>Height:</b>	15.2mm
<b>Stripped wire length:</b>	8mm
<b>Operating temperature:</b>	-40...105°C

## Additional information

<b>Gross weight:</b>	0.012 kg
----------------------	----------