



|                        |                          |
|------------------------|--------------------------|
| <b>Symbol:</b>         | NS39-W8P                 |
| <b>Product groups:</b> | Raster signal connectors |

## Product specifications

|                             |            |
|-----------------------------|------------|
| <b>Type of connector:</b>   | wire-board |
| <b>Connector:</b>           | socket     |
| <b>Kind of connector:</b>   | male       |
| <b>Manufacturer series:</b> | NS39       |
| <b>Number of pins:</b>      | 8          |
| <b>Current rating:</b>      | 7A         |
| <b>Rated voltage:</b>       | 0.25kV     |
| <b>Spatial orientation:</b> | straight   |
| <b>Electrical mounting:</b> | THT        |
| <b>Contacts pitch:</b>      | 3.96mm     |

|                                 |            |
|---------------------------------|------------|
| <b>Connector pinout layout:</b> | 1x8        |
| <b>Contact plating:</b>         | tinned     |
| <b>Locking system:</b>          | latch      |
| <b>Flammability rating:</b>     | UL94V-0    |
| <b>Enclosure material:</b>      | polyamide  |
| <b>Operating temperature:</b>   | -25...85°C |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.002 kg |
|----------------------|----------|