



<b>Symbol:</b>	TBG-5-PB-3P/GN
<b>Product groups:</b>	Terminal blocks

## Product specifications

<b>Type of connector:</b>	pluggable terminal block
<b>Connector:</b>	socket
<b>Kind of connector:</b>	male
<b>Current rating:</b>	15A
<b>Rated voltage:</b>	0.3kV
<b>Number of pins:</b>	3
<b>Spatial orientation:</b>	straight
<b>Connector variant:</b>	without side walls
<b>Mechanical mounting:</b>	on PCBs
<b>Electrical mounting:</b>	THT
<b>Contact material:</b>	brass
<b>Contact plating:</b>	tinned
<b>Colour:</b>	green
<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	polyamide
<b>Depth:</b>	8mm

## Product card TBG-5-PB-3P/GN

---

<b>Length:</b>	15.24mm
<b>Connector pinout layout:</b>	1x3
<b>Contacts pitch:</b>	5.08mm
<b>Number of ways:</b>	3
<b>Locking system:</b>	latch
<b>Height:</b>	12.3mm
<b>Connectors features:</b>	assembling possibility
<b>Soldering temperature:</b>	250°C / 5 s
<b>Operating temperature:</b>	-40...105°C

## Additional information

<b>Gross weight:</b>	0.001 kg
----------------------	----------