

|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | TBW-5-13P/GN    |
| <b>Product groups:</b> | Terminal blocks |

## Product specifications

|                                 |                          |
|---------------------------------|--------------------------|
| <b>Type of connector:</b>       | pluggable terminal block |
| <b>Connector:</b>               | plug                     |
| <b>Kind of connector:</b>       | female                   |
| <b>Current rating:</b>          | 15A                      |
| <b>Rated voltage:</b>           | 0.3kV                    |
| <b>Spatial orientation:</b>     | straight                 |
| <b>Mechanical mounting:</b>     | for cable                |
| <b>Electrical mounting:</b>     | screw terminal           |
| <b>Contact material:</b>        | brass                    |
| <b>Contact plating:</b>         | tinned                   |
| <b>Colour:</b>                  | green                    |
| <b>Flammability rating:</b>     | UL94V-0                  |
| <b>Body material:</b>           | polyamide                |
| <b>Depth:</b>                   | 17.7mm                   |
| <b>Connector pinout layout:</b> | 1x13                     |
| <b>Wire cross-section:</b>      | 2.5mm <sup>2</sup>       |
| <b>Contacts pitch:</b>          | 5.08mm                   |

|                               |             |
|-------------------------------|-------------|
| <b>Number of ways:</b>        | 13          |
| <b>Locking system:</b>        | latch       |
| <b>Number of terminals:</b>   | 13          |
| <b>Height:</b>                | 15.2mm      |
| <b>Stripped wire length:</b>  | 8mm         |
| <b>Operating temperature:</b> | -40...105°C |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.001 kg |
|----------------------|----------|