

## Karta výrobku NXW-12K

---



|                         |                          |
|-------------------------|--------------------------|
| <b>Symbol:</b>          | NXW-12K                  |
| <b>Skupina výrobků:</b> | Raster signal connectors |

### Parametry výrobku

|                                  |            |
|----------------------------------|------------|
| <b>Type of connector:</b>        | wire-board |
| <b>Connector:</b>                | socket     |
| <b>Kind of connector:</b>        | male       |
| <b>Number of pins:</b>           | 12         |
| <b>Spatial orientation:</b>      | angled 90° |
| <b>Electrical mounting:</b>      | THT        |
| <b>Contacts pitch:</b>           | 2mm        |
| <b>Connector pinout layout:</b>  | 1x12       |
| <b>Contact plating:</b>          | tinned     |
| <b>Flammability rating:</b>      | UL94V-0    |
| <b>Maximum current:</b>          | 1A         |
| <b>Max. operating voltage:</b>   | 100V       |
| <b>Max. contact resistance::</b> | 20mΩ       |
| <b>Enclosure material:</b>       | polyamide  |
| <b>Width:</b>                    | 26mm       |

**Operating  
temperature:**

-25...85°C

## **Doplňková informace**

**Hmotnost brutto:**

0.00076 kg