



<b>Symbol:</b>	TB-3.5-P-3P/GY
<b>Skupina výrobků:</b>	Terminal blocks

## Parametry výrobku

<b>Type of connector:</b>	PCB terminal block
<b>Connector:</b>	terminal
<b>Current rating:</b>	10A
<b>Rated voltage:</b>	0.3kV
<b>Spatial orientation:</b>	angled 90°
<b>Connector variant:</b>	with wire protector
<b>Mechanical mounting:</b>	on PCBs
<b>Electrical mounting:</b>	screw terminal, THT
<b>Contact material:</b>	brass
<b>Contact plating:</b>	tinned
<b>Colour:</b>	grey
<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	polyamide
<b>Depth:</b>	6.8mm
<b>Length:</b>	10.5mm
<b>Connector pinout layout:</b>	1x3

<b>Wire cross-section:</b>	0.5...1mm <sup>2</sup>
<b>Contacts pitch:</b>	3.5mm
<b>Number of ways:</b>	3
<b>Height:</b>	8.4mm
<b>Stripped wire length:</b>	5mm
<b>Connectors features:</b>	assembling possibility
<b>Soldering temperature:</b>	250°C / 5 s
<b>Operating temperature:</b>	-40...105°C

## Doplňková informace

<b>Hmotnost brutto:</b>	0.001196 kg
-------------------------	-------------