



| | |
|-------------------------|-----------------|
| Symbol: | TBG-5-KB-4P/GN |
| Skupina výrobků: | Terminal blocks |

Parametry výrobku

| | |
|-----------------------------|--------------------------|
| Type of connector: | pluggable terminal block |
| Connector: | socket |
| Kind of connector: | male |
| Current rating: | 15A |
| Rated voltage: | 0.3kV |
| Number of pins: | 4 |
| Spatial orientation: | angled 90° |
| Connector variant: | without side walls |
| Mechanical mounting: | on PCBs |
| Electrical mounting: | THT |
| Contact material: | brass |
| Contact plating: | tinned |
| Colour: | green |
| Flammability rating: | UL94V-0 |
| Body material: | polyamide |
| Depth: | 12.3mm |

Karta výrobku TBG-5-KB-4P/GN

| | |
|---------------------------------|------------------------|
| Length: | 20.32mm |
| Connector pinout layout: | 1x4 |
| Contacts pitch: | 5.08mm |
| Number of ways: | 4 |
| Locking system: | friction lock |
| Height: | 8mm |
| Connectors features: | assembling possibility |
| Soldering temperature: | 250°C / 5 s |
| Operating temperature: | -40...105°C |

Doplňková informace

| | |
|-------------------------|-------------|
| Hmotnost brutto: | 0.001466 kg |
|-------------------------|-------------|