

## Product card NS25-W4K

---



|                        |                          |
|------------------------|--------------------------|
| <b>Symbol:</b>         | NS25-W4K                 |
| <b>Product groups:</b> | Raster signal connectors |

### Product specifications

|                                  |            |
|----------------------------------|------------|
| <b>Type of connector:</b>        | wire-board |
| <b>Connector:</b>                | socket     |
| <b>Kind of connector:</b>        | male       |
| <b>Number of pins:</b>           | 4          |
| <b>Manufacturer series:</b>      | NS25       |
| <b>Current rating:</b>           | 3A         |
| <b>Rated voltage:</b>            | 0.25kV     |
| <b>Spatial orientation:</b>      | angled 90° |
| <b>Electrical mounting:</b>      | THT        |
| <b>Contacts pitch:</b>           | 2.54mm     |
| <b>Connector pinout layout:</b>  | 1x4        |
| <b>Contact plating:</b>          | tinned     |
| <b>Flammability rating:</b>      | UL94V-0    |
| <b>Max. contact resistance::</b> | 10mΩ       |
| <b>Enclosure material:</b>       | polyamide  |
| <b>A dimension:</b>              | 10.16mm    |

**B dimension:** 7.62mm

**Leads dimensions:** 0.64x0.64x3.3mm

**Operating temperature:** -25...85°C

## **Additional information**

**Gross weight:** 0 kg