



| | |
|----------------|--------|
| Symbol: | NXG-07 |
|----------------|--------|

| | |
|------------------------|--------------------------|
| Product groups: | Raster signal connectors |
|------------------------|--------------------------|

Product specifications

| | |
|---------------------------|------------|
| Type of connector: | wire-board |
|---------------------------|------------|

| | |
|-------------------|------|
| Connector: | plug |
|-------------------|------|

| | |
|---------------------------|--------|
| Kind of connector: | female |
|---------------------------|--------|

| | |
|------------------------|---|
| Number of pins: | 7 |
|------------------------|---|

| | |
|-----------------------------|-----|
| Manufacturer series: | NXG |
|-----------------------------|-----|

| | |
|-----------------------------|-----------|
| Mechanical mounting: | for cable |
|-----------------------------|-----------|

| | |
|------------------------|-----|
| Contacts pitch: | 2mm |
|------------------------|-----|

| | |
|---------------------------------|-----|
| Connector pinout layout: | 1x7 |
|---------------------------------|-----|

| | |
|-----------------------------|---------|
| Flammability rating: | UL94V-0 |
|-----------------------------|---------|

| | |
|--------------------------------|--------------|
| Body material: | polyamide |
| Connector variant: | w/o contacts |
| Max. operating voltage: | 100V |
| Width: | 15.8mm |
| A dimension: | 12mm |
| Operating temperature: | -25...85°C |

Additional information

| | |
|----------------------|------|
| Gross weight: | 0 kg |
|----------------------|------|