



|                        |                    |
|------------------------|--------------------|
| <b>Symbol:</b>         | TACTM-24N-REEL     |
| <b>Product groups:</b> | Microswitches TACT |

## Product specifications

|                                  |                  |
|----------------------------------|------------------|
| <b>Type of switch:</b>           | microswitch TACT |
| <b>Contacts configuration:</b>   | SPST-NO          |
| <b>Number of positions:</b>      | 2                |
| <b>DC contacts rating @R:</b>    | 50mA / 12V DC    |
| <b>Mounting:</b>                 | SMT              |
| <b>Illumination:</b>             | none             |
| <b>Operating Force:</b>          | 1.6N             |
| <b>Body dimensions:</b>          | 12x12mm          |
| <b>Button height:</b>            | 4.3mm            |
| <b>Terminal pitch:</b>           | 5x12.4mm         |
| <b>Operating temperature:</b>    | -20...70°C       |
| <b>Button shape:</b>             | round            |
| <b>Actuator colour:</b>          | black            |
| <b>Leads:</b>                    | for soldering    |
| <b>Max. contact resistance::</b> | 100mΩ            |

**Min. insulation  
resistance:**

0.1GΩ

**Soldering  
temperature:**

260°C / 5 s

## **Additional information**

**Gross weight:**

0.001 kg