

## Product card TACTS-24K-F

---



<b>Symbol:</b>	TACTS-24K-F
<b>Product groups:</b>	Microswitches TACT

### Product specifications

<b>Type of switch:</b>	microswitch TACT
<b>Contacts configuration:</b>	SPST-NO
<b>Number of positions:</b>	2
<b>Stable positions number:</b>	1
<b>DC contacts rating @R:</b>	50mA / 12V DC
<b>Mounting:</b>	THT
<b>Illumination:</b>	none
<b>Operating Force:</b>	0.69N
<b>Body dimensions:</b>	12x12mm
<b>Button height:</b>	7.3mm
<b>Switching method:</b>	OFF-(ON)
<b>Terminal pitch:</b>	5x12.5mm
<b>Operating temperature:</b>	-25...70°C
<b>Button shape:</b>	square
<b>Actuator colour:</b>	black

## Product card TACTS-24K-F

---

<b>Button size:</b>	3.8x3.8mm
<b>Leads:</b>	for PCB, straight
<b>Max. contact resistance::</b>	50mΩ
<b>Min. insulation resistance:</b>	0.1GΩ
<b>Soldering temperature:</b>	250°C

## Additional information

<b>Gross weight:</b>	0.001 kg
----------------------	----------