

Product card TB-5-PD-3P/GY



| | |
|----------------------------------|----------------------|
| Symbol: | TB-5-PD-3P/GY |
| Manufacturer part number: | AC142R-03P-5.08-GRAY |
| Product groups: | Terminal blocks |

Product specifications

| | |
|-----------------------------|--------------------|
| Type of connector: | PCB terminal block |
| Connector: | terminal |
| Current rating: | 10A |
| Rated voltage: | 0.25kV |
| Spatial orientation: | angled 90° |
| Connector variant: | with lever |
| Mechanical mounting: | on PCBs |
| Electrical mounting: | spring clamp, THT |
| Contact material: | brass |
| Contact plating: | tinned |
| Colour: | grey |
| Flammability rating: | UL94V-0 |
| Body material: | polyamide |
| Depth: | 13.88mm |
| Length: | 17.78mm |

| | |
|---------------------------------|--------------------|
| Connector pinout layout: | 1x3 |
| Wire cross-section: | 0.5mm ² |
| Contacts pitch: | 5.08mm |
| Number of ways: | 3 |
| Height: | 10.6mm |
| Stripped wire length: | 10mm |
| Soldering temperature: | 250°C / 5 s |
| Operating temperature: | -40...105°C |

Additional information

| | |
|----------------------|----------|
| Gross weight: | 0.003 kg |
|----------------------|----------|