

## Karta výrobku NLSG-3X3

---



|  |                          |
|--|--------------------------|
| <b>Symbol:</b>                         | NLSG-3X3                 |
| <b>product.pip.manufacturerSymbol:</b> | NSLG-3X3                 |
| <b>Skupina výrobků:</b>                | Raster signal connectors |

### Parametry výrobku

|                                 |  |
|---------------------------------|--|
| <b>Type of connector:</b>       | wire-wire                                    |
| <b>Connector:</b>               | plug/socket                                  |
| <b>Kind of connector:</b>       | male/female                                  |
| <b>Number of pins:</b>          | 9  |
| <b>Manufacturer series:</b>     | NLS  |
| <b>Rated voltage:</b>           | 0.6kV  |
| <b>Mechanical mounting:</b>     | for cable, for panel mounting, snap fastener |
| <b>Contacts pitch:</b>          | 6.35mm                                       |
| <b>Connector pinout layout:</b> | 3x3  |
| <b>Connector variant:</b>       | w/o contacts                                 |
| <b>Locking system:</b>          | latch  |
| <b>Flammability rating:</b>     | UL94V-2                                      |
| <b>Connectors features:</b>     | designed for any type of contacts            |
| <b>Operating temperature:</b>   | -25...85°C                                   |

**Enclosure material:** polyamide

## Doplňková informace

**Hmotnost brutto:** 0.00698 kg