



|                         |                    |
|-------------------------|--------------------|
| <b>Symbol:</b>          | TACT-65K-F         |
| <b>Skupina výrobků:</b> | Microswitches TACT |

## Parametry výrobku

|                                 |                  |
|---------------------------------|------------------|
| <b>Type of switch:</b>          | microswitch TACT |
| <b>Contacts configuration:</b>  | SPST-NO          |
| <b>Number of positions:</b>     | 2                |
| <b>Stable positions number:</b> | 1                |
| <b>DC contacts rating @R:</b>   | 50mA / 12V DC    |
| <b>Mounting:</b>                | THT              |
| <b>Illumination:</b>            | none             |
| <b>Operating Force:</b>         | 1N               |
| <b>Body dimensions:</b>         | 6x6mm            |
| <b>Button height:</b>           | 5mm              |
| <b>Switching method:</b>        | OFF-(ON)         |
| <b>Terminal pitch:</b>          | 4.5x6.5mm        |
| <b>Operating temperature:</b>   | -25...70°C       |
| <b>Button shape:</b>            | round            |
| <b>Actuator colour:</b>         | black            |

|                                    |                   |
|------------------------------------|-------------------|
| <b>Leads:</b>                      | for PCB, straight |
| <b>Max. contact resistance::</b>   | 50mΩ              |
| <b>Min. insulation resistance:</b> | 0.1GΩ             |
| <b>Soldering temperature:</b>      | 250°C             |

## Doplňková informace

|                         |             |
|-------------------------|-------------|
| <b>Hmotnost brutto:</b> | 0.000264 kg |
|-------------------------|-------------|