



|                         |                    |
|-------------------------|--------------------|
| <b>Symbol:</b>          | TACTMS-24N-F       |
| <b>Skupina výrobků:</b> | Microswitches TACT |

## Parametry výrobku

|                                 |                  |
|---------------------------------|------------------|
| <b>Type of switch:</b>          | microswitch TACT |
| <b>Contacts configuration:</b>  | SPST-NO          |
| <b>Number of positions:</b>     | 2                |
| <b>Stable positions number:</b> | 1                |
| <b>DC contacts rating @R:</b>   | 50mA / 12V DC    |
| <b>Mounting:</b>                | SMT              |
| <b>Illumination:</b>            | none             |
| <b>Operating Force:</b>         | 1.6N             |
| <b>Body dimensions:</b>         | 12x12mm          |
| <b>Button height:</b>           | 7.3mm            |
| <b>Switching method:</b>        | OFF-(ON)         |
| <b>Terminal pitch:</b>          | 5x15mm           |
| <b>Operating temperature:</b>   | -25...70°C       |
| <b>Button shape:</b>            | square           |
| <b>Actuator colour:</b>         | yellow           |

**Leads:** for PCB

**Max. contact resistance::** 50mΩ

## Doplňková informace

**Hmotnost brutto:** 0.000826 kg