



<b>Symbol:</b>	1T1206
<b>Product groups:</b>	Microswitches TACT

## Product specifications

<b>Type of switch:</b>	microswitch TACT
<b>Contacts configuration:</b>	SPST-NO
<b>Number of positions:</b>	2
<b>Stable positions number:</b>	1
<b>DC contacts rating @R:</b>	50mA / 12V DC
<b>Mounting:</b>	SMT
<b>Illumination:</b>	none
<b>Operating Force:</b>	1.8N

## Product card 1T1206

---

<b>Body material:</b>	stainless steel, thermoplastic
<b>Body dimensions:</b>	4.5x6.1mm
<b>Button height:</b>	1.3mm
<b>Switching method:</b>	OFF-(ON)
<b>Terminal pitch:</b>	3.4x5.8mm
<b>Operating temperature:</b>	-20...70°C
<b>Button shape:</b>	rectangular
<b>Actuator colour:</b>	blue
<b>Terminals material:</b>	brass
<b>Terminals plating:</b>	silver plated
<b>Leads:</b>	for PCB
<b>Contact material:</b>	phosphor bronze
<b>Max. contact resistance::</b>	100mΩ
<b>Contact plating:</b>	silver plated
<b>Electrical life:</b>	50000 cycles

## Additional information

<b>Gross weight:</b>	0 kg
----------------------	------