



<b>Symbol:</b>	TB-5.0-PT-3P
<b>Product groups:</b>	Terminal blocks

## Product specifications

<b>Type of connector:</b>	PCB terminal block
<b>Connector:</b>	terminal
<b>Current rating:</b>	11A
<b>Rated voltage:</b>	0.25kV
<b>Spatial orientation:</b>	straight
<b>Connector variant:</b>	with lever
<b>Mechanical mounting:</b>	on PCBs
<b>Electrical mounting:</b>	spring clamp, THT
<b>Contact material:</b>	brass
<b>Contact plating:</b>	tinned
<b>Colour:</b>	green
<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	polyamide 66
<b>Wire size:</b>	22AWG...18AWG
<b>Depth:</b>	13mm
<b>Length:</b>	15.15mm

<b>Connector pinout layout:</b>	1x3
<b>Wire cross-section:</b>	0.5mm <sup>2</sup>
<b>Contacts pitch:</b>	5mm
<b>Number of ways:</b>	3
<b>Height:</b>	11.4mm
<b>Conform to the norm:</b>	UL
<b>Operating temperature:</b>	-55...100°C

## Additional information

<b>Gross weight:</b>	0.002 kg
----------------------	----------