

## Product card WLK-4MINI

---



|                        |                           |
|------------------------|---------------------------|
| <b>Symbol:</b>         | WLK-4MINI                 |
| <b>Product groups:</b> | Microswitches SNAP ACTION |

### Product specifications

|                                  |                          |
|----------------------------------|--------------------------|
| <b>Type of switch:</b>           | microswitch SNAP ACTION  |
| <b>AC contacts rating @R:</b>    | 5A / 250V AC             |
| <b>Switches features:</b>        | with lever (with roller) |
| <b>Contacts configuration:</b>   | SPDT                     |
| <b>Max. contact resistance::</b> | 30mΩ                     |
| <b>Switching method:</b>         | ON-(ON)                  |
| <b>Number of positions:</b>      | 2                        |
| <b>Stable positions number:</b>  | 1                        |

## Product card WLK-4MINI

---

|                                    |                 |
|------------------------------------|-----------------|
| <b>IP rating:</b>                  | IP40            |
| <b>Leads:</b>                      | for soldering   |
| <b>Body dimensions:</b>            | 19.8x6.4x10.6mm |
| <b>Operating temperature:</b>      | -25...65°C      |
| <b>Operating Force:</b>            | 1.5N            |
| <b>Lever length:</b>               | 17mm            |
| <b>Electrical life:</b>            | 30000 cycles    |
| <b>Min. insulation resistance:</b> | 0.1GΩ           |
| <b>Terminal pitch:</b>             | 7.3mm           |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.003 kg |
|----------------------|----------|