



|                        |                   |
|------------------------|-------------------|
| <b>Symbol:</b>         | PS10BYL           |
| <b>Product groups:</b> | Standard Switches |

## Product specifications

|                                 |               |
|---------------------------------|---------------|
| <b>Type of switch:</b>          | push-button   |
| <b>Number of positions:</b>     | 2             |
| <b>Stable positions number:</b> | 1             |
| <b>Contacts configuration:</b>  | SPST-NO       |
| <b>AC contacts rating @R:</b>   | 1A / 250V AC  |
| <b>Switching method:</b>        | OFF-(ON)      |
| <b>Illumination:</b>            | none          |
| <b>Leads:</b>                   | for soldering |

## Product card PS10BYL

---

|                                  |                  |
|----------------------------------|------------------|
| <b>Electrical life:</b>          | 50000 cycles     |
| <b>Max. contact resistance::</b> | 20mΩ             |
| <b>Button shape:</b>             | prominent, round |
| <b>Mounting hole dimensions:</b> | Ø7mm             |
| <b>Body material:</b>            | metal, plastic   |
| <b>Actuator colour:</b>          | yellow           |
| <b>Height above panel:</b>       | 12mm             |
| <b>Mounting:</b>                 | on panel         |
| <b>Body dimensions:</b>          | Ø9.2x27.5mm      |
| <b>Operating temperature:</b>    | -25...70°C       |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.003 kg |
|----------------------|----------|