



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | RSM2013C3BK     |
| <b>Product groups:</b> | Rocker Switches |

## Product specifications

|                                 |              |
|---------------------------------|--------------|
| <b>Type of switch:</b>          | ROCKER       |
| <b>Contacts configuration:</b>  | DPST         |
| <b>Number of positions:</b>     | 2            |
| <b>Stable positions number:</b> | 2            |
| <b>Switching method:</b>        | ON-OFF       |
| <b>AC contacts rating @R:</b>   | 3A / 250V AC |
| <b>Key button colour:</b>       | black        |
| <b>Illumination:</b>            | none         |

|                                  |              |
|----------------------------------|--------------|
| <b>Max. contact resistance::</b> | 35mΩ         |
| <b>Body colour:</b>              | black        |
| <b>Leads:</b>                    | connectors   |
| <b>Leads dimensions:</b>         | 4.8x0.8mm    |
| <b>Electrical life:</b>          | 10000 cycles |
| <b>Mounting hole dimensions:</b> | 18x13.1mm    |
| <b>Button marking:</b>           | O-I          |
| <b>Shape:</b>                    | rectangular  |
| <b>Operating temperature:</b>    | -30...80°C   |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.005 kg |
|----------------------|----------|