



|                        |                          |
|------------------------|--------------------------|
| <b>Symbol:</b>         | NCDG-02                  |
| <b>Product groups:</b> | Raster signal connectors |

## Product specifications

|                                 |              |
|---------------------------------|--------------|
| <b>Type of connector:</b>       | wire-board   |
| <b>Connector:</b>               | plug         |
| <b>Kind of connector:</b>       | female       |
| <b>Number of pins:</b>          | 2            |
| <b>Mechanical mounting:</b>     | for cable    |
| <b>Contacts pitch:</b>          | 2.54mm       |
| <b>Connector pinout layout:</b> | 1x2          |
| <b>Flammability rating:</b>     | UL94V-0      |
| <b>Connector variant:</b>       | w/o contacts |

|                                |            |
|--------------------------------|------------|
| <b>Locking system:</b>         | latch      |
| <b>Max. operating voltage:</b> | 0.25kV     |
| <b>Enclosure material:</b>     | PBT        |
| <b>A dimension:</b>            | 5.1mm      |
| <b>B dimension:</b>            | 2.5mm      |
| <b>Operating temperature:</b>  | -25...85°C |

## Additional information

|                      |      |
|----------------------|------|
| <b>Gross weight:</b> | 0 kg |
|----------------------|------|