



|                                  |                          |
|----------------------------------|--------------------------|
| <b>Symbol:</b>                   | NLSG-3X4                 |
| <b>Manufacturer part number:</b> | NSLG-3X4                 |
| <b>Product groups:</b>           | Raster signal connectors |

## Product specifications

|                             |                                              |
|-----------------------------|----------------------------------------------|
| <b>Type of connector:</b>   | wire-wire                                    |
| <b>Connector:</b>           | plug/socket                                  |
| <b>Kind of connector:</b>   | male/female                                  |
| <b>Number of pins:</b>      | 12                                           |
| <b>Manufacturer series:</b> | NLS                                          |
| <b>Rated voltage:</b>       | 0.6kV                                        |
| <b>Mechanical mounting:</b> | for cable, for panel mounting, snap fastener |
| <b>Contacts pitch:</b>      | 6.35mm                                       |

|                                 |                                   |
|---------------------------------|-----------------------------------|
| <b>Connector pinout layout:</b> | 3x4                               |
| <b>Connector variant:</b>       | w/o contacts                      |
| <b>Locking system:</b>          | latch                             |
| <b>Flammability rating:</b>     | UL94V-2                           |
| <b>Connectors features:</b>     | designed for any type of contacts |
| <b>Operating temperature:</b>   | -25...85°C                        |
| <b>Enclosure material:</b>      | polyamide                         |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.009 kg |
|----------------------|----------|