



|                |           |
|----------------|-----------|
| <b>Symbol:</b> | ZL2019-20 |
|----------------|-----------|

|                        |             |
|------------------------|-------------|
| <b>Product groups:</b> | Pin headers |
|------------------------|-------------|

## Product specifications

|                           |            |
|---------------------------|------------|
| <b>Type of connector:</b> | pin strips |
|---------------------------|------------|

|                   |            |
|-------------------|------------|
| <b>Connector:</b> | pin header |
|-------------------|------------|

|                           |      |
|---------------------------|------|
| <b>Kind of connector:</b> | male |
|---------------------------|------|

|                        |    |
|------------------------|----|
| <b>Number of pins:</b> | 20 |
|------------------------|----|

|                             |     |
|-----------------------------|-----|
| <b>Electrical mounting:</b> | THT |
|-----------------------------|-----|

|                             |          |
|-----------------------------|----------|
| <b>Spatial orientation:</b> | straight |
|-----------------------------|----------|

|                         |    |
|-------------------------|----|
| <b>Maximum current:</b> | 3A |
|-------------------------|----|

|                        |        |
|------------------------|--------|
| <b>Contacts pitch:</b> | 2.54mm |
|------------------------|--------|

|                                 |      |
|---------------------------------|------|
| <b>Connector pinout layout:</b> | 1x20 |
|---------------------------------|------|

|                         |             |
|-------------------------|-------------|
| <b>Contact plating:</b> | gold-plated |
|-------------------------|-------------|

|                                |             |
|--------------------------------|-------------|
| <b>Connector variant:</b>      | double deck |
| <b>Max. operating voltage:</b> | 250V AC     |
| <b>B dimension:</b>            | 6mm         |
| <b>C dimension:</b>            | 3mm         |
| <b>E dimension:</b>            | 1.27mm      |
| <b>L1 dimension:</b>           | 10.4mm      |
| <b>Overall length:</b>         | 19.4mm      |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.002 kg |
|----------------------|----------|