



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | TSSM1022A1      |
| <b>Product groups:</b> | Toggle Switches |

## Product specifications

|                                 |               |
|---------------------------------|---------------|
| <b>Type of switch:</b>          | toggle        |
| <b>Number of positions:</b>     | 2             |
| <b>Stable positions number:</b> | 2             |
| <b>Contacts configuration:</b>  | SPDT          |
| <b>Switching method:</b>        | ON-ON         |
| <b>AC contacts rating @R:</b>   | 1A / 250V AC  |
| <b>Leads:</b>                   | for soldering |
| <b>Operating temperature:</b>   | -55...65°C    |

|                                  |               |
|----------------------------------|---------------|
| <b>Kind of toggle:</b>           | round         |
| <b>Mounting hole dimensions:</b> | Ø5mm          |
| <b>Knob height:</b>              | 9.4mm         |
| <b>Max. contact resistance::</b> | 20mΩ          |
| <b>Body dimensions:</b>          | 8.3x5.2x8.6mm |
| <b>Electrical life:</b>          | 20000 cycles  |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.003 kg |
|----------------------|----------|