



|                        |                        |
|------------------------|------------------------|
| <b>Symbol:</b>         | KS-31                  |
| <b>Product groups:</b> | Key Switches and Locks |

## Product specifications

|                                  |                                                                  |
|----------------------------------|------------------------------------------------------------------|
| <b>Type of switch:</b>           | key switch                                                       |
| <b>Stable positions number:</b>  | 2                                                                |
| <b>Switching method:</b>         | OFF-ON                                                           |
| <b>Contacts configuration:</b>   | SPST                                                             |
| <b>Switches features:</b>        | key with the random code, the key can be removed at any position |
| <b>Number of positions:</b>      | 2                                                                |
| <b>Mounting hole dimensions:</b> | Ø12mm                                                            |
| <b>Key shape:</b>                | flat                                                             |

|                                   |               |
|-----------------------------------|---------------|
| <b>Kind of wrench:</b>            | unsymmetrical |
| <b>Body material:</b>             | zinc alloy    |
| <b>AC contacts rating @R:</b>     | 1A / 125V AC  |
| <b>Mechanical rotation angle:</b> | 90°           |
| <b>Number of terminals:</b>       | 2             |
| <b>Overall length:</b>            | 30.5mm        |
| <b>Terminals plating:</b>         | silver plated |
| <b>Contact plating:</b>           | silver plated |

## Additional information

|                      |         |
|----------------------|---------|
| <b>Gross weight:</b> | 0.02 kg |
|----------------------|---------|