



|                        |                          |
|------------------------|--------------------------|
| <b>Symbol:</b>         | NS25-G10                 |
| <b>Product groups:</b> | Raster signal connectors |

## Product specifications

|                             |            |
|-----------------------------|------------|
| <b>Type of connector:</b>   | wire-board |
| <b>Connector:</b>           | plug       |
| <b>Kind of connector:</b>   | female     |
| <b>Number of pins:</b>      | 10         |
| <b>Manufacturer series:</b> | NS25       |
| <b>Current rating:</b>      | 3A         |
| <b>Rated voltage:</b>       | 0.25kV     |
| <b>Mechanical mounting:</b> | for cable  |
| <b>Contacts pitch:</b>      | 2.54mm     |

|                                 |              |
|---------------------------------|--------------|
| <b>Connector pinout layout:</b> | 1x10         |
| <b>Flammability rating:</b>     | UL94V-0      |
| <b>Connector variant:</b>       | w/o contacts |
| <b>Enclosure material:</b>      | polyamide    |
| <b>A dimension:</b>             | 22.86mm      |
| <b>B dimension:</b>             | 25.9mm       |
| <b>Operating temperature:</b>   | -25...85°C   |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.001 kg |
|----------------------|----------|