



|                 |                    |
|-----------------|--------------------|
| Symbol:         | TACT-24K-F         |
| Product groups: | Microswitches TACT |

Product specifications

|                          |                  |
|--------------------------|------------------|
| Type of switch:          | microswitch TACT |
| Contacts configuration:  | SPST-NO          |
| Number of positions:     | 2                |
| Stable positions number: | 1                |
| DC contacts rating @R:   | 50mA / 12V DC    |
| Mounting:                | THT              |
| Illumination:            | none             |
| Operating Force:         | 1.27N            |

|                                    |                   |
|------------------------------------|-------------------|
| <b>Body dimensions:</b>            | 12x12mm           |
| <b>Button height:</b>              | 4.3mm             |
| <b>Switching method:</b>           | OFF-(ON)          |
| <b>Terminal pitch:</b>             | 5x12.5mm          |
| <b>Operating temperature:</b>      | -25...70°C        |
| <b>Button shape:</b>               | round             |
| <b>Actuator colour:</b>            | black             |
| <b>Leads:</b>                      | for PCB, straight |
| <b>Max. contact resistance::</b>   | 50mΩ              |
| <b>Min. insulation resistance:</b> | 0.1GΩ             |
| <b>Soldering temperature:</b>      | 250°C             |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.001 kg |
|----------------------|----------|