



|                        |                 |
|------------------------|-----------------|
| <b>Symbol:</b>         | TSP104AA1       |
| <b>Product groups:</b> | Toggle Switches |

### Product specifications

|                                 |               |
|---------------------------------|---------------|
| <b>Type of switch:</b>          | toggle        |
| <b>Number of positions:</b>     | 2             |
| <b>Stable positions number:</b> | 1             |
| <b>Contacts configuration:</b>  | SPST          |
| <b>Switching method:</b>        | (ON)-OFF      |
| <b>AC contacts rating @R:</b>   | 10A / 250V AC |
| <b>Leads:</b>                   | M3 screws     |
| <b>Operating temperature:</b>   | -25...85°C    |

|                                  |              |
|----------------------------------|--------------|
| <b>Kind of toggle:</b>           | round        |
| <b>Mounting hole dimensions:</b> | Ø12.2mm      |
| <b>Knob height:</b>              | 17.5mm       |
| <b>Max. contact resistance::</b> | 50mΩ         |
| <b>Body dimensions:</b>          | 29x15.8x19mm |
| <b>Electrical life:</b>          | 10000 cycles |
| <b>Related items:</b>            | TSPC02       |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.023 kg |
|----------------------|----------|