



|                        |                          |
|------------------------|--------------------------|
| <b>Symbol:</b>         | NLSW-1X3                 |
| <b>Product groups:</b> | Raster signal connectors |

## Product specifications

|                                 |             |
|---------------------------------|-------------|
| <b>Type of connector:</b>       | wire-wire   |
| <b>Connector:</b>               | plug        |
| <b>Kind of connector:</b>       | male/female |
| <b>Number of pins:</b>          | 3           |
| <b>Manufacturer series:</b>     | NLS         |
| <b>Rated voltage:</b>           | 0.6kV       |
| <b>Mechanical mounting:</b>     | for cable   |
| <b>Contacts pitch:</b>          | 6.35mm      |
| <b>Connector pinout layout:</b> | 1x3         |

## Product card NLSW-1X3

---

|                               |                                   |
|-------------------------------|-----------------------------------|
| <b>Connector variant:</b>     | w/o contacts                      |
| <b>Locking system:</b>        | latch                             |
| <b>Flammability rating:</b>   | UL94V-2                           |
| <b>Connectors features:</b>   | designed for any type of contacts |
| <b>Operating temperature:</b> | -25...85°C                        |
| <b>Enclosure material:</b>    | polyamide                         |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.002 kg |
|----------------------|----------|