



|                        |                      |
|------------------------|----------------------|
| <b>Symbol:</b>         | PS28B-2              |
| <b>Product groups:</b> | Push Button Switches |

## Product specifications

|                                 |                  |
|---------------------------------|------------------|
| <b>Type of switch:</b>          | vandal resistant |
| <b>Number of positions:</b>     | 2                |
| <b>Stable positions number:</b> | 1                |
| <b>Contacts configuration:</b>  | SPST-NO          |
| <b>AC contacts rating @R:</b>   | 2A / 250V AC     |
| <b>IP rating:</b>               | IP40             |
| <b>Switching method:</b>        | OFF-(ON)         |
| <b>Leads:</b>                   | screw terminals  |

|                                  |                 |
|----------------------------------|-----------------|
| <b>Electrical life:</b>          | 50000 cycles    |
| <b>Max. contact resistance::</b> | 20mΩ            |
| <b>Button shape:</b>             | flat            |
| <b>Mounting hole dimensions:</b> | Ø19mm           |
| <b>Body colour:</b>              | silver          |
| <b>Body material:</b>            | stainless steel |
| <b>Operating temperature:</b>    | -25...85°C      |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.021 kg |
|----------------------|----------|