



|                        |                        |
|------------------------|------------------------|
| <b>Symbol:</b>         | KS-38                  |
| <b>Product groups:</b> | Key Switches and Locks |

## Product specifications

|                                 |  |
|---------------------------------|--|
| <b>Type of switch:</b>          | key switch   |
| <b>Stable positions number:</b> | 2  |
| <b>Switching method:</b>        | OFF-ON   |
| <b>Contacts configuration:</b>  | SPST   |
| <b>Switches features:</b>       | key with the same code, the key can be removed at any position |
| <b>Number of positions:</b>     | 2  |
| <b>Mounting hole diameter:</b>  | Ø12mm  |
| <b>Key shape:</b>               | round  |

|                                   |               |
|-----------------------------------|---------------|
| <b>Kind of wrench:</b>            | unsymmetrical |
| <b>Body material:</b>             | zinc alloy    |
| <b>AC contacts rating @R:</b>     | 1A / 125V AC  |
| <b>Mechanical rotation angle:</b> | 90°           |
| <b>Number of terminals:</b>       | 2             |
| <b>Overall length:</b>            | 19.3mm        |
| <b>Terminals plating:</b>         | silver plated |
| <b>Contact plating:</b>           | silver plated |

## Additional information

|                      |          |
|----------------------|----------|
| <b>Gross weight:</b> | 0.019 kg |
|----------------------|----------|