



<b>Symbol:</b>	TB-3.5-P-2P-GY
----------------	----------------

<b>Product groups:</b>	Terminal blocks
------------------------	-----------------

## Product specifications

<b>Type of connector:</b>	PCB terminal block
---------------------------	--------------------

<b>Connector:</b>	terminal
-------------------	----------

<b>Current rating:</b>	12A
------------------------	-----

<b>Rated voltage:</b>	0.3kV
-----------------------	-------

<b>Spatial orientation:</b>	angled 90°
-----------------------------	------------

<b>Mechanical mounting:</b>	on PCBs
-----------------------------	---------

<b>Electrical mounting:</b>	screw terminal, THT
-----------------------------	---------------------

<b>Contact material:</b>	brass
--------------------------	-------

<b>Contact plating:</b>	tinned
-------------------------	--------

<b>Colour:</b>	dark grey
----------------	-----------

<b>Flammability rating:</b>	UL94V-0
<b>Body material:</b>	PBT
<b>Depth:</b>	7.4mm
<b>Length:</b>	7mm
<b>Connector pinout layout:</b>	1x2
<b>Wire cross-section:</b>	1mm <sup>2</sup>
<b>Contacts pitch:</b>	3.5mm
<b>Number of ways:</b>	2
<b>Height:</b>	9.1mm
<b>Connectors features:</b>	assembling possibility
<b>Operating temperature:</b>	-40...105°C

## Additional information

<b>Gross weight:</b>	0.001 kg
----------------------	----------