



Symbol:	TB-5.08-P-2P/BL
----------------	-----------------

Product groups:	Terminal blocks
------------------------	-----------------

Product specifications

Type of connector:	PCB terminal block
---------------------------	--------------------

Connector:	terminal
-------------------	----------

Current rating:	16A
------------------------	-----

Rated voltage:	0.25kV
-----------------------	--------

Spatial orientation:	angled 90°
-----------------------------	------------

Connector variant:	with wire protector
---------------------------	---------------------

Mechanical mounting:	on PCBs
-----------------------------	---------

Electrical mounting:	screw terminal, THT
-----------------------------	---------------------

Contact material:	brass
--------------------------	-------

Contact plating:	tinned
-------------------------	--------

Colour:	blue
Flammability rating:	UL94V-0
Body material:	PBT
Depth:	7.6mm
Length:	10.16mm
Connector pinout layout:	1x2
Wire cross-section:	1.5mm ²
Contacts pitch:	5.08mm
Number of ways:	2
Height:	10mm
Stripped wire length:	5mm
Connectors features:	assembling possibility
Conform to the norm:	CE
Soldering temperature:	250°C / 5 s
Operating temperature:	-30...120°C

Additional information

Gross weight:	0.002 kg
----------------------	----------