

Karta výrobku 1T1206



| | |
|-------------------------|--------------------|
| Symbol: | 1T1206 |
| Skupina výrobků: | Microswitches TACT |

Parametry výrobku

| | |
|---------------------------------|--------------------------------|
| Type of switch: | microswitch TACT |
| Contacts configuration: | SPST-NO |
| Number of positions: | 2 |
| Stable positions number: | 1 |
| DC contacts rating @R: | 50mA / 12V DC |
| Mounting: | SMT |
| Illumination: | none |
| Operating Force: | 1.8N |
| Body material: | stainless steel, thermoplastic |
| Body dimensions: | 4.5x6.1mm |
| Button height: | 1.3mm |
| Switching method: | OFF-(ON) |
| Terminal pitch: | 3.4x5.8mm |
| Operating temperature: | -20...70°C |
| Button shape: | rectangular |

| | |
|----------------------------------|-----------------|
| Actuator colour: | blue |
| Terminals material: | brass |
| Terminals plating: | silver plated |
| Leads: | for PCB |
| Contact material: | phosphor bronze |
| Max. contact resistance:: | 100mΩ |
| Contact plating: | silver plated |
| Electrical life: | 50000 cycles |

Doplňková informace

| | |
|-------------------------|-------------|
| Hmotnost brutto: | 0.000126 kg |
|-------------------------|-------------|