



|                         |                          |
|-------------------------|--------------------------|
| <b>Symbol:</b>          | NCDW-03                  |
| <b>Skupina výrobků:</b> | Raster signal connectors |

### Parametry výrobku

|                                  |            |
|----------------------------------|------------|
| <b>Type of connector:</b>        | wire-board |
| <b>Connector:</b>                | socket     |
| <b>Kind of connector:</b>        | male       |
| <b>Number of pins:</b>           | 3          |
| <b>Spatial orientation:</b>      | straight   |
| <b>Electrical mounting:</b>      | THT        |
| <b>Contacts pitch:</b>           | 2.54mm     |
| <b>Connector pinout layout:</b>  | 1x3        |
| <b>Contact plating:</b>          | tinned     |
| <b>Flammability rating:</b>      | UL94V-0    |
| <b>Maximum current:</b>          | 2.5A       |
| <b>Locking system:</b>           | latch      |
| <b>Max. operating voltage:</b>   | 0.25kV     |
| <b>Max. contact resistance::</b> | 20mΩ       |
| <b>Enclosure material:</b>       | polyamide  |

|                               |            |
|-------------------------------|------------|
| <b>A dimension:</b>           | 5.08mm     |
| <b>B dimension:</b>           | 10.17mm    |
| <b>Operating temperature:</b> | -25...85°C |

## Doplňková informace

|                         |             |
|-------------------------|-------------|
| <b>Hmotnost brutto:</b> | 0.000642 kg |
|-------------------------|-------------|