



| | |
|-------------------------|-----------------|
| Symbol: | TB-5.0-PT-2P |
| Skupina výrobků: | Terminal blocks |

Parametry výrobku

| | |
|-----------------------------|--------------------|
| Type of connector: | PCB terminal block |
| Connector: | terminal |
| Current rating: | 11A |
| Rated voltage: | 0.25kV |
| Spatial orientation: | straight |
| Connector variant: | with lever |
| Mechanical mounting: | on PCBs |
| Electrical mounting: | spring clamp, THT |
| Contact material: | brass |
| Contact plating: | tinned |
| Colour: | green |
| Flammability rating: | UL94V-0 |
| Body material: | polyamide 66 |
| Wire size: | 22AWG...18AWG |
| Depth: | 13mm |
| Length: | 10.15mm |

| | |
|---------------------------------|--------------------|
| Connector pinout layout: | 1x2 |
| Wire cross-section: | 0.5mm ² |
| Contacts pitch: | 5mm |
| Number of ways: | 2 |
| Height: | 11.4mm |
| Conform to the norm: | UL |
| Operating temperature: | -55...100°C |

Doplňková informace

| | |
|-------------------------|------------|
| Hmotnost brutto: | 0.00161 kg |
|-------------------------|------------|