

## Product card TACTM-64N-F-REEL

---



<b>Symbol:</b>	TACTM-64N-F-REEL
<b>Manufacturer part number:</b>	TACTM-64N-F-R
<b>Product groups:</b>	Microswitches TACT

## Product specifications

<b>Type of switch:</b>	microswitch TACT
<b>Contacts configuration:</b>	SPST-NO
<b>Number of positions:</b>	2
<b>Stable positions number:</b>	1
<b>DC contacts rating @R:</b>	50mA / 12V DC
<b>Mounting:</b>	SMT
<b>Illumination:</b>	none
<b>Operating Force:</b>	1.6N
<b>Body dimensions:</b>	6x6mm
<b>Button height:</b>	4.3mm
<b>Switching method:</b>	OFF-(ON)
<b>Terminal pitch:</b>	4.5x9mm
<b>Operating temperature:</b>	-30...85°C

## Product card TACTM-64N-F-REEL

---

<b>Button shape:</b>	round
<b>Actuator colour:</b>	black
<b>Leads:</b>	for soldering
<b>Max. contact resistance::</b>	50mΩ
<b>Min. insulation resistance:</b>	0.1GΩ
<b>Mechanical durability:</b>	100000 cycles
<b>Soldering temperature:</b>	235°C / 5 s
<b>Number of pieces on reel:</b>	1000pcs.

## Additional information

<b>Gross weight:</b>	0 kg
----------------------	------