

## Product card WLK-4MINI

---



|                        |                           |
|------------------------|---------------------------|
| <b>Symbol:</b>         | WLK-4MINI                 |
| <b>Product groups:</b> | Microswitches SNAP ACTION |

## Product specifications

|                                  |                          |
|----------------------------------|--------------------------|
| <b>Type of switch:</b>           | microswitch SNAP ACTION  |
| <b>AC contacts rating @R:</b>    | 5A / 250V AC             |
| <b>Switches features:</b>        | with lever (with roller) |
| <b>Contacts configuration:</b>   | SPDT                     |
| <b>Max. contact resistance::</b> | 30mΩ                     |
| <b>Switching method:</b>         | ON-(ON)                  |
| <b>Number of positions:</b>      | 2                        |
| <b>Stable positions number:</b>  | 1                        |
| <b>IP rating:</b>                | IP40                     |
| <b>Leads:</b>                    | for soldering            |
| <b>Body dimensions:</b>          | 19.8x6.4x10.6mm          |
| <b>Operating temperature:</b>    | -25...65°C               |
| <b>Operating Force:</b>          | 1.5N                     |
| <b>Lever length:</b>             | 17mm                     |

**Electrical life:** 30000 cycles

**Min. insulation resistance:** 0.1GΩ

**Terminal pitch:** 7.3mm

## **Additional information**

**Gross weight:** 0.003 kg