

## Karta výrobku KS-32

---



|                         |                        |
|-------------------------|------------------------|
| <b>Symbol:</b>          | KS-32                  |
| <b>Skupina výrobků:</b> | Key Switches and Locks |

### Parametry výrobku

|                                   |  |
|-----------------------------------|--|
| <b>Type of switch:</b>            | key switch   |
| <b>Stable positions number:</b>   | 2  |
| <b>Switching method:</b>          | OFF-ON   |
| <b>Contacts configuration:</b>    | SPST   |
| <b>Switches features:</b>         | key with the random code, the key can be removed at any position |
| <b>Number of positions:</b>       | 2  |
| <b>Mounting hole diameter:</b>    | Ø19mm  |
| <b>Key shape:</b>                 | flat   |
| <b>Kind of wrench:</b>            | unsymmetrical  |
| <b>Body material:</b>             | zinc alloy   |
| <b>AC contacts rating @R:</b>     | 1A / 125V AC   |
| <b>Mechanical rotation angle:</b> | 90°  |
| <b>Number of terminals:</b>       | 2  |

|                           |               |
|---------------------------|---------------|
| <b>Overall length:</b>    | 43.5mm        |
| <b>Terminals plating:</b> | silver plated |
| <b>Contact plating:</b>   | silver plated |

## Doplňková informace

|                         |           |
|-------------------------|-----------|
| <b>Hmotnost brutto:</b> | 0.0493 kg |
|-------------------------|-----------|