

## Karta výrobku SR2611415FN

---



|                         |                 |
|-------------------------|-----------------|
| <b>Symbol:</b>          | SR2611415FN     |
| <b>Skupina výrobků:</b> | Rotary Switches |

### Parametry výrobku

|                                    |                    |
|------------------------------------|--------------------|
| <b>Type of switch:</b>             | rotary             |
| <b>Number of positions:</b>        | 4                  |
| <b>Stable positions number:</b>    | 4                  |
| <b>AC contacts rating @R:</b>      | 0.3A / 125V AC     |
| <b>Poles number:</b>               | 1                  |
| <b>Indexed positions:</b>          | 30°                |
| <b>Leads:</b>                      | for soldering      |
| <b>Contact material:</b>           | brass              |
| <b>Switching method:</b>           | BBM (non-shorting) |
| <b>Max. contact resistance::</b>   | 30mΩ               |
| <b>Min. insulation resistance:</b> | 0.1GΩ              |
| <b>Mechanical durability:</b>      | 6000 cycles        |
| <b>Shaft surface:</b>              | smooth             |
| <b>Shaft diameter:</b>             | 6mm                |

|                               |            |
|-------------------------------|------------|
| <b>Shaft length:</b>          | 15mm       |
| <b>Fastening thread:</b>      | 3/8"-32NEF |
| <b>Switching torque:</b>      | 4.9Ncm     |
| <b>Operating temperature:</b> | -20...70°C |

## Doplňková informace

|                         |            |
|-------------------------|------------|
| <b>Hmotnost brutto:</b> | 0.00884 kg |
|-------------------------|------------|