

## Karta výrobku TACTMS-24N/O

---



|  |                       |
|--|-----------------------|
| <b>Symbol:</b>                         | TACTMS-24N/O          |
| <b>product.pip.manufacturerSymbol:</b> | DS1042-01-21KYAX25010 |
| <b>Skupina výrobků:</b>                | Microswitches TACT    |

### Parametry výrobku

|                                |                  |
|--------------------------------|------------------|
| <b>Type of switch:</b>         | microswitch TACT |
| <b>Contacts configuration:</b> | SPST-NO          |
| <b>Number of positions:</b>    | 2                |
| <b>DC contacts rating @R:</b>  | 50mA / 12V DC    |
| <b>Mounting:</b>               | SMT              |
| <b>Illumination:</b>           | none             |
| <b>Operating Force:</b>        | 1.6N             |
| <b>Body dimensions:</b>        | 12x12mm          |
| <b>Button height:</b>          | 4.3mm            |
| <b>Switching method:</b>       | OFF-(ON)         |
| <b>Terminal pitch:</b>         | 5x15mm           |
| <b>Operating temperature:</b>  | -25...70°C       |
| <b>Button shape:</b>           | square           |
| <b>Actuator colour:</b>        | yellow           |

**Leads:** for PCB

**Max. contact resistance::** 50mΩ

## Doplňková informace

**Hmotnost brutto:** 0.000812 kg