



| | |
|-------------------------|-----------------|
| Symbol: | TB-5.0-P-2P/GY |
| Skupina výrobků: | Terminal blocks |

Parametry výrobku

| | |
|---------------------------------|----------------------------------|
| Type of connector: | PCB terminal block |
| Connector: | terminal |
| Current rating: | 16A |
| Rated voltage: | 0.25kV |
| Spatial orientation: | angled 90° |
| Connector variant: | cross screw, with wire protector |
| Mechanical mounting: | on PCBs |
| Electrical mounting: | screw terminal, THT |
| Contact material: | brass |
| Contact plating: | tinned |
| Colour: | grey |
| Flammability rating: | UL94V-0 |
| Body material: | PBT |
| Depth: | 7.6mm |
| Length: | 10mm |
| Connector pinout layout: | 1x2 |

| | |
|-------------------------------|------------------------|
| Wire cross-section: | 1.5mm ² |
| Contacts pitch: | 5mm |
| Number of ways: | 2 |
| Height: | 10mm |
| Stripped wire length: | 5mm |
| Connectors features: | assembling possibility |
| Conform to the norm: | CE |
| Soldering temperature: | 250°C / 5 s |
| Operating temperature: | -30...120°C |

Doplňková informace

| | |
|-------------------------|-------------|
| Hmotnost brutto: | 0.001562 kg |
|-------------------------|-------------|